

TRACKSIDE

RAILTRACK ACCEPTED



2.2kW to 6kW (2.7kVA to 7.5kVA) 110 Volt CTE.

Unique stacking frame with anti ballast plate and metal long run fuel tank.

Honda OHV Oil alert petrol engines.

Railtrack Accepted.

Option - Economy lightweight lighting tower that clamps onto the generator frame.

Diesel Sets

Also available are a range of EU noise compliant diesel powered generators. From 4kVA to 125kVA. 110 Volt CTE, 3 Phase or 650 Volt single phase.

220 Amp DC Welder. Railtrack Accepted.

Vanguard OHV V twin with oil guard.

Heavy duty 4 man lift 2 wheel trolley with foam filled pneumatic tyres.

NEW 250 Amp version available ideal for continuous wire feed operation..



60 Amp 12 & 24 Volt DC Fast charger.

Complete with ammeter and post terminals, this self powered battery charger packs a big enough punch to start a loco or any large plant.

Honda GX160 Oil alert petrol engine.

NEW 80 Amp version



2 & 4 way Audible Warning Devices

for use with approved petrol and diesel powered generators.

Railtrack Accepted design.

Sentinel Welding Validator

To be used with a suitable DC welder to accurately set and re-set the welder. The Sentinel can be positioned away from the welding machine and nearer to the operator.




Harrington Generators International Ltd.
Ravenstor Road, Wirksworth, Derbyshire. England. DE4 4FY

Tel: 01629 824284 · Fax: 01629 824613

Email: sales@harringtongen.co.uk
www.harrington-international.co.uk



TRACKSIDE GENERATORS

Output		PETROL Engine	Model Codes Full Frame 	Dimensions Full Frame L x W x H (mm)	Weight (Full Frame kg)	Tank Capacity (litres)	Running Time approximate hrs/tank @ 3/4 load)	Noise Level (dB(A) @ 7m)	Sockets 110 Volt CTE (BS4343) Standard arrangement		
kW	kVA								16 amp	32 amp	63 amp
2.2	2.7	Honda GX160	HSF - R22	610x410x475	38	11	10	71	1	1	
2.4	3.0	Honda GX160	HSF - R24	610x410x475	40	11	9	72	1	1	
2.8	3.5	Honda GX200	HSF - R28	610x410x475	41	11	8	73	1	1	
3.0	3.75	Honda GX240	HSF - R30	780x480x560	62	16	10	73	1	1	
3.5	4.4	Honda GX270	HSF - R35	780x480x560	62	16	10	74	1	1	
4.0	5.0	Honda GX270	HSF - R40	780x480x560	64	16	9	74	2	1	
5.0	6.25	Honda GX340	HSF - R50	780x480x560	70	16	7	75	2	1	1
416.0	7.5	Honda GX390	HSF - R60	780x480x560	77	16	7	75	2	1	1

TRACKSIDE Audible Warning Devices

Output	Input	Klaxons	C.Breaker	Weight	Size (L x W x H)	Rating
2 x 16 amp sockets	1 x 32 amp plug	2x111 dB(A) @ 1 metre	32 amp	12 kg	300mm x 300mm x 400mm High	3.5 kWatt
4 x 16 amp sockets	1 x 63 amp plug		63 amp	17 kg		7.0 kWatt

Harrington 'TRACKSIDE' range of power equipment is 'RAILTRACK APPROVED'. Copy certificates available.

Also made by Harringtons are 650 Volt AMF Railguard mobile and static sets. Vandal resistant Railguard AMF ECE3 (Tin12) specification, telecommunication, military and other specialised applications. SPITFIRE Welders. SILENT KNIGHT Super Silent Generators and over 300 standard petrol and diesel generators.

Manufactured un England by Harrington Generators Ltd.